

Package: ARDECO (via r-universe)

August 29, 2024

Type Package

Title Annual Regional Database of the European Commission (ARDECO)

Version 2.0.0

Description A set of functions to access the 'ARDECO' (Annual Regional Database of the European Commission) data directly from the official ARDECO public repository through the exploitation of the 'ARDECO' APIs. The APIs are completely transparent to the user and the provided functions provide a direct access to the 'ARDECO' data. The 'ARDECO' database is a collection of variables related to demography, employment, labour market, domestic product, capital formation. Each variable can be exposed in one or more units of measure as well as refers to total values plus economic sectors. The description of the 'ARDECO' database can be found at the following URL <https://urban.jrc.ec.europa.eu/ardeco>.

Depends R (>= 4.2.0),

Imports httr, ghql, rjstat, jsonlite, stringr, dplyr, tidyr

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation no

Author Carmelo Attardo [cre], Giuseppe Bucciarelli [aut], European Commission, JRC [cph]

Maintainer Carmelo Attardo <carmelo.attardo@ec.europa.eu>

Date/Publication 2024-08-28 03:50:06 UTC

Repository <https://attarco.r-universe.dev>

RemoteUrl <https://github.com/cran/ARDECO>

RemoteRef HEAD

RemoteSha 49ad2aaba987e71bd81c00e6ab2418548eb77048

Contents

ARDECO packages	2
ardeco_get_dataset_data	3
ardeco_get_dataset_list	4
ardeco_get_variable_list	5
Index	6

ARDECO packages	<i>ARDECO packages</i>
-----------------	------------------------

Description

This package provide a set of functions to access the ARDECO data directly from the official ARDECO public repository through the exploitation of the ARDECO API. The API are completely transparent to the user and the provided functions provide a direct access to the ARDECO data. The ARDECO (Annual Regional Database of the European Commission) database is a collection of variables related to demography, employment, labour market, domestic product, capital formation. Each variable can be exposed in one or more units of measure as well as refers to total values plus specific values related to different dimensions defined for each variable. For example, sex, age or economic sectors (NACE sectors as defined by EUROSTAT). The description of the ARDECO database can be found at the following URL <https://urban.jrc.ec.europa.eu/ardeco>

The exposed funtions

This package provides three functions which are linked between them and have to be used in the following way.

- **ardeco_get_variable_list** - to recover the list of the available variables with related description.
- **ardeco_get_dataset_list** - After having identified the variable of interest, it's possible to identify the list of datasets included into the variable of interest. This function return the list of the dimensions defined into the selected variable with the possible values.
- **ardeco_get_dataset_data** - To recover the data related to a variable it's possible to do it by using just the variable code (recovering all variable data) or filtering it using unit, nuts version, levels, year, nutscode and all optional additional dimension (like sector, age, sex) recovered by ardeco_get_dataset_list.

Examples

```
ardeco_get_variable_list()
ardeco_get_dataset_list('SNPTN')
ardeco_get_dataset_data('SNPTN', version=2021, level='0', nutscode='LT', year='2020')
```

```
ardeco_get_dataset_data
    ardeco_get_dataset_data
```

Description

The function recover the data via API of the dataset specified in input applying the optional filters and return the list of data in data frame format.

Usage

```
ardeco_get_dataset_data(variable, ...)
```

Arguments

variable	mandatory: the code of variable
...	Other optional parameters to filter according to the different dimensions. This can be: version, level, nutscode, year, unit and the additional dimensions depending by the selected variable

Details

Each parameter have to be passed using notation **<param-name>='<param-value>'**.

For some Optional parameters it can be used a special notation increasing the filtering options.

FILTERING OPTION FOR PARAMETER **nutscode**

It's possible to require values with nuts codes satisfying multiple conditions, using the character ',' to separate the different conditions.

For example: **nutscode='EE,IT'** return only the nuts codes related starting with 'EE' or 'IT', i.e. return all values for Estonia and Italy.

FILTERING OPTION FOR PARAMETERS **year** and **level**

The parameters **year** and **level** are numeric parameters.

A numeric parameter can have a simple value. In this case the function return the values in which the specific parameter is EQUAL to the inserted value.

For example: **level=0** return the values at NUTS0 level.

It's possible to require values satisfying multiple conditions, using the character ',' to require values for different year or level.

For example: **level='0,2'** return the values for level 0 and level 2. Remember to use quote to define the list of values.

It's also possible to filter data defining an interval of years/levels. It can be defined using this notation: **c(min-max)** where min and max are the minimum and maximum values. Remember to use quote to define the values interval.

For example: **year='2000-2005'** return the values for the years starting from 2000 to 2005.

Value

This function return a data frame including the data related to the selected dataset. The data frame include the following fields:

- VARIABLE: code of the variable
- VERSION: nuts version of NUTS code.
- LEVEL: level of NUTS code. From 0 to 3 represent NUTS0-3 level; 4 refers to Metropolitan regions, 9 refers data at EU level.
- NUTSCODE: code of the territorial unit of reference. It's one of the NUTS code (see EUROSTAT)
- YEAR: year of reference of the value.
- DIM(s): one or more columns depending by the dimensions defined for the selected dataset
- UNIT: unit of measure of the value.
- VALUE: value of the selected variable related to the date, sector, territory_id, unit, variable

Examples

```
ardeco_get_dataset_data('SNPTN', version=2021, level=0, nutscode='IT', year=2020, sex='Males')
ardeco_get_dataset_data('SUVGD', version=2021, level='0,2', nutscode='EE', year='2018-2020')
```

```
ardeco_get_dataset_list
                         ardeco_get_dataset_list
```

Description

The function return the list of dataset linked to a variable through the ARDECO API by defining the variable code. For each dataset it's returned the code of variable, the unit of measure, the nuts version and the eventual additional dimensions (like sector, sex, age classes) for which the data is available.

Usage

```
ardeco_get_dataset_list(var_code)
```

Arguments

var_code one of the code returned by ardeco_get_variable_list()

Value

The set of datasets related to the selected variable. Each dataset is described by: - var: variable code - unit: unit of measure - vers: available nuts version - additional dimensions: additional dimensions (like sector, sex, age class) and related permitted values

Examples

```
ardeco_get_dataset_list('SNPTN')
```

ardeco_get_variable_list
ardeco_get_variable_list

Description

This function return the list of all available ARDECO variable recovered through the ARDECO API. The function returns the list of code and description of each variable. Code will be used to recover the list of datasets and also the data of a variable.

Usage

```
ardeco_get_variable_list()
```

Details

return the list of the available variables exposed by ARDECO database

Value

This function returns the list of the code and the description of each available variables. The code have to be used in the next functions to recover the datasets and the data values

Examples

```
ardeco_get_variable_list()
```

Index

ARDECO packages, [2](#)
ardec_get_dataset_data, [3](#)
ardec_get_dataset_list, [4](#)
ardec_get_variable_list, [5](#)